

# ABIMIG® A Lightweight Air-Cooled

200/300/400 Amp Torches

## Ordering Instructions for Complete Torches

<u>A</u>	<u>F</u>	<u>3</u>	<u>15</u>	<u>C</u>	<u>T</u>	<u>35</u>	<u>L1</u>	<u>S</u>
Torch Model	Handle	Amperage	Cable Length	Cable Type	Nozzle	Wire Size	Back End	Handle
<b>Torch Model</b> A - ABIMIG®	<b>Handle</b> F - Fixed Neck	<b>Amperage</b> 2 - 200 Amp (255 Model) 3 - 300 Amp (355 Model) 4 - 400 Amp (415 Model)	<b>Cable Length</b> 10 Feet 15 Feet 20 Feet 25 Feet	<b>Cable Type</b> No Letter = Lightweight C = Copper	<b>Nozzle</b> T - Threaded	<b>Wire Size</b> 35 - .035 Inches <sup>1</sup> 45 - .045 Inches 52 - .052 Inches <sup>2</sup> 62 - .062 Inches <sup>2</sup> 78 - .078 Inches <sup>3</sup> 94 - .094 Inches <sup>3</sup>	<b>Back End</b> E - Euro L - Lincoln External gas L1 - Lincoln 10, 74 & 84 Series L2 - Lincoln Power MIG HT - Hobart/Tweco M - Miller Standard M1 - Miller Multimatic <sup>2</sup> X - No connector kit installed	<b>Handle</b> S - Short Trigger



Binzel S.A. DE C. V.  
 Municipio Pabellon de Arteaga 102  
 Valle De Aguascalientes, 20358  
 San Francisco de los Romo, Ags. Mexico  
 Phone: +52(499) 973.0133  
 Fax: +52(499) 973.1388  
 Email: info@binzel.com.mx

ABICOR BINZEL USA, Inc.  
 650 Medimmune Ct., Suite 110  
 Frederick, MD 21703-8619  
 Phone: 1.800.542.4867  
 Fax: 1.301.846.4497  
 Email: customerservice@abicorusa.com

[www.binzel-abicor.com](http://www.binzel-abicor.com)